



Intelligent Stand-Alone Direct Thermal Label Printer

Discover efficiency and reliability with our TSDP5000XPLUS

10.1" colour touch screen, compact design, easy label change, powerful processor and versatile label formats for diverse needs.

Model: TSDP5000XPLUS



The TSDP5000XPLUS is a compact yet powerful stand-alone label printer ideal for high-use food labelling applications.

The TSDP5000XPLUS advances the legacy of the DP5000 series, combining proven reliability with enhanced performance to meet current and future business labelling requirements. Brimming with powerful features, the TSDP5000XPLUS is the smart new choice for businesses looking for reliable and efficient thermal label printing.

A 10.1" crystal clear capacitive touchscreen and intuitive user interface enable operators to manage product labelling requirements including 1D and 2D barcodes, COOL, PEAL, Nutrition Information Panel.

▲ 10.1″ Touchscreen

TSDP5000XPLUS Label Printers feature a crystal clear, fullcolour 10.1" TFT WSVGA capacitive touchscreen and the user interface can be configured to suit your needs.

The operator touch screen offers a standard user interface across both the TSDP5000X and SM5500X series weigh labeller range – facilitating interdepartmental team member training and technical support.

To ensure the best viewing and ergonomic operating position, the display can easily be adjusted to suit different counter and operator heights.

TSDP5000XPLUS Features Summary

- 10.1" full-colour capacitive touchscreen display
- reliable durability designed for high-use environments
- compact space-saving stand-alone printing
- energy efficient compliance to 80 PLUS
- easy front-loading label roll change
- peel and present labelling with internal rewind
- powerful Quad Core Processor
- fast high-resolution direct thermal printing
- large memory
- adjustable user display rotates left/right, up/down
- programmable function and preset buttons
- helpful on-screen operator prompts
- remote diagnostics and support
- a large range of label formats including dual labels
- supports
 - > Country of Origin Labelling (COOL)
 - > Plain English Allergen Labelling (PEAL)
 - > Nutritional Information Panel (NIP) Labelling
 - images on labels
 - > 1D and 2D barcode printing

OPTIONS

- Atria back office management software
- wireless module

Proven Reliability - Fast High Volume Printing

This robust industrial grade front-loading 300 dpi printer delivers high-resolution, high volume printing with impressive efficiency up to 150 mm per second. Evolving from the TSDP5000E series, it has a proven track record to be a business critical, reliable workhorse in single point sensitive production environments.

Smart Space-Saving Design

The front loading label cassette enables both printing and label changes to be carried out from the front of the machine. This, coupled with a small footprint, means the TSDP5000XPLUS requires minimal bench space.



Specifications may change without notice


Intelligent Stand-Alone Thermal Direct Label Printer

Model : TSDP5000XPLUS


SPECIFICATIONS


| Model Number | TSDP5000XPLUS | TSDP5000XPLUSLL |
|---------------------------|--|----------------------------|
| | Die-Cut Label Printer | Linerless Label Printer |
| Operator Display | 10.1" TFT WSVGA capacitive touchscreen | |
| Display Size (pixels) | 1024 (W) × 600 (D) | |
| Display Rotation | \pm 30 degrees left and right; 80 degrees up and down | |
| Label | | |
| Labeller Type | Liner (Die-Cut Labels) | Linerless with Auto-Cutter |
| Print Speed - Maximum | 150 mm per second | 150 mm per second |
| Print Width - Maximum | 80 mm | 80 mm |
| Print Length - Maximum | 350 mm | 350 mm |
| Label Width - Maximum | 80 mm | 80 mm |
| Label Roll Size - Maximum | 125 mm OD (100 mm OD if using rewind) | 125 mm |
| Label Core Size | 40 mm | 40 mm |
| Printer | | |
| Print Method | Direct Thermal | |
| Printer Type | Industrial | |
| Print Resolution | 300 dpi | |
| Peel and Present | Yes - Standard | Yes - Standard |
| Internal Rewinder | Yes - Standard | No |
| Barcode Type | Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, RSS, PDF417 (For Receipt Only), GS1, QR code, Datamatrix | |
| Energy Efficiency | Compliance to 80PLUS Power Saving - with configurable power saving options | |
| Communication Type | | |
| Ethernet | Yes - Standard | |
| WiFi | Yes - Optional (2.4/5 GHz Wireless LAN 802.11 a / b / g / ac) | |
| Standard Interfaces | Ethernet, 4 x USB, SD Socket | |
| Options | Atria Back-Office Management Software | |
| Overall Dimensions (mm) | 290 (W) x 423 (D) x 420 (H) | |
| Net Weight | 12 kg | |

DIMENSIONS (mm)



TOP VIEW





SIDE VIEW

Freephone: 0800 800 379

enquiries@wedderburn.co.nz

www.wedderburn.co.nz

∠ Labelling Equipment

Weighing Scales. Packaging Equipment. Labelling Equipment. Labels. Food Equipment. POS Solutions. Maintenance & Repairs.